



Data table	
Speed at free air:	1390 ±10% rpm at 220V 1570 ±10% rpm at 240V
Temprise:	Free air 108°C at 244V Locked rotor 156°C at 240V
Fergas lab report no:	MT 1956
Airflow at free air:	203m ³ /h at 240V in 20°C
Voltage range:	220–240V 50Hz
Insulation class:	H
IP class:	00
See also Fergas guide lines for product use	

Tolerances in accordance with ISO 2768-m

Confidential: Property of Fergas AB, Linköping, Sweden. Not to be handed over to, copied or used by third party. Two or three dimensional reproduction of contents, to be authorized by Fergas AB.

Item no.	Qty	Description	Material	Dimension	Notes
6	1	LABEL FERGAS	PAPER	K9000	PROD.W-OP.
5	1	GROMET Ø3.5	SILICONE	K1525	50±5 SHORE
4	1	ENDBEARING CPL	NBR	55077	BRONZBEARING
3	1	HUNAN KELI MOTOR FER 16	YJ64-20A	K3022	230V. 50Hz
2	1	HOUSING NCB-HL60x240	HX300LAD	55630	Ø4.8(4x)Ø3.2(4x)
1	1	WHEEL NC60x240 R	ALU	55410	

Designed by	Drawn by	Copied by	Checked by	Standard	Approved by	Scale	Replaces	Replaced by
LE	LE	-	-	-	EC	1:1	-	-

FERGAS Linköping Sweden
 Title: BLOWER NC60
 NCB-HL60x240 R 16-90 K3022
 Revision date: 14-05-09
 Date: 14-05-09
 Dwg. no.: W51609 A

Pos.	Qty.	Notes	Date	Ch. by	Appr.